

# Standards and Service Limits

## 5. Engine/Cylinder Head, Valve Train

	MEASUREMENT	STANDARD (NEW)	SERVICE LIMIT	
Compression	250 min <sup>-1</sup> (rpm) and wide-open throttle	Nominal Minimum Maximum variation	1226 kPa (12.5 kg/cm <sup>2</sup> , 178 psi) 931 kPa (9.5 kg/cm <sup>2</sup> , 135 psi) 196 kPa (2 kg/cm <sup>2</sup> , 28 psi)	
Cylinder head	Warpage Height	99.95—100.05 (3.935—3.938)	0.05 (0.002)	
Camshaft	End play	0.05—0.15 (0.002—0.006)	0.50 (0.020)	
	Oil clearance	0.05—0.089 (0.002—0.0035)	0.150 (0.006)	
	Runout	0.03 (0.001) max.	0.04 (0.002)	
	Cam lobe height	IN 1. F20A2:	38.526 (1.5167)	—
		2. F20A3:	38.526 (1.5167)	—
		3. F20A5:	38.741 (1.5252)	—
		4. F20A6:	38.526 (1.5167)	—
		5. F20A8:	38.741 (1.5252)	—
		6. F22A2:	38.741 (1.5252)	—
		7. F22A3:	39.167 (1.5420) M/T 38.741 (1.5252) A/T	—
	8. F22A6:	38.741 (1.5252)	—	
	9. F22A7:	39.167 (1.5420)	—	
	10. F22A8:	38.741 (1.5252)	—	
11. F22A9:	38.741 (1.5252)	—		
12. F20A7:	38.741 (1.5252)	—		
13. F20Z3:	38.741 (1.5252)	—		
EX	1. F20A2:	38.778 (1.5266)	—	
	2. F20A3:	38.778 (1.5266)	—	
	3. F20A5:	38.972 (1.5343)	—	
	4. F20A6:	38.778 (1.5266)	—	
	5. F20A8:	38.972 (1.5343)	—	
	6. F22A2:	38.972 (1.5343)	—	
	7. F22A3:	39.356 (1.5494) M/T 38.972 (1.5343) A/T	—	
8. F22A6:	38.972 (1.5343)	—		
9. F22A7:	39.356 (1.5494)	—		
10. F22A8:	38.972 (1.5343)	—		
11. F22A9:	38.972 (1.5343)	—		
12. F20A7:	38.972 (1.5353)	—		
13. F20Z3:	38.972 (1.5353)	—		
Valve	Valve clearance	IN 0.23—0.28 (0.0091—0.0110) EX 0.27—0.32 (0.0106—0.1259)	—	
	Valve stem O.D.	IN 5.485—5.495 (0.2159—0.2163) EX 5.450—5.460 (0.2145—0.2149)	5.455 (0.2148) 5.420 (0.2133)	
	Stem-to-guide clearance	IN 0.020—0.045 (0.0007—0.0017) EX 0.055—0.080 (0.0021—0.0031)	0.075 (0.0029) 0.12 (0.0047)	
Valve seat	Width	IN and EX 1.25—1.55 (0.049—0.0610)	2.00 (0.0787)	
	Valve stem installed height	IN 48.245—48.715 (1.8994—1.9179) EX 50.315—50.785 (1.9809—1.9994)	— —	
Valve spring	Free length	IN (NH) 56.28 (2.2157)* <sup>1</sup> 54.82 (2.1582)* <sup>1</sup> 53.15 (2.0925)* <sup>2</sup>	— — —	
		(CH) 56.26 (2.2150)* <sup>1</sup> 54.81 (2.1578)* <sup>1</sup> 53.16 (2.0929)* <sup>2</sup>	— — —	
		(AS) 54.82 (2.1582)* <sup>1</sup>	—	
			—	
			—	

- |                                  |   |
|----------------------------------|---|
| 1. F20A2: 2.0 ℓ CARB with CATA   | 7. F22A3: 2.2 ℓ PGM-FI with CATA                |
| 2. F20A3: 2.0 ℓ CARB             | 8. F22A6: 2.2 ℓ PGM-FI with CATA for 5D KQ      |
| 3. F20A5: 2.0 ℓ PGM-FI           | 9. F22A7: 2.2 ℓ PGM-FI with CATA for 5D EC M/T  |
| 4. F20A6: 2.0 ℓ CARB with CATA   | 10. F22A8: 2.2 ℓ PGM-FI with CATA for 5D EC A/T |
| 5. F20A8: 2.0 ℓ PGM-FI with CATA | 11. F22A9: 2.2 ℓ PGM-FI with CATA for KQ        |
| 6. F22A2: 2.2 ℓ PGM-FI           | 12. F20A7: 2.0 ℓ PGM-FI with CATA for KB other  |
|                                  | 13. F20Z3: 2.0 ℓ PGM-FI with CATA for 5D EC     |

NH: NIHON HATSUJO  
CH: CHUO HATSUJO  
AS: ASSOCIATED SPRING

- \*1: 2.0 ℓ CARB  
\*2: 2.0 ℓ and 2.2 ℓ PGM-FI

## 5. Engine/Cylinder Head, Valve Train

MEASUREMENT		STANDARD (NEW)	SERVICE LIMIT
Valve spring	Free length EX (AS): NH): CH):	56.28 (2.2157)*1 55.78 (2.1960)*2 55.80 (2.1968)*2	— — —
Valve guide	I.D. Valve guide installed height IN and EX IN EX	5.515—5.530 (0.2171—0.2177) 23.75—24.25 (0.9148—0.9547) 15.05—15.55 (0.5925—0.6122)	5.53 (0.2177) — —
Rocker arm	Arm-to-shaft clearance IN EX	0.017—0.050 (0.0007—0.0020) 0.018—0.054 (0.0007—0.0021)	0.080 (0.0031) 0.080 (0.0031)

\*1: 2.0 ℓ CARB

\*2: 2.0 ℓ and 2.2 ℓ PGM-FI

AS: ASSOCIATED SPRING

NH: NIHON HATUJO

CH: CHUO HATSUJO

## 5. Engine/Engine Block

MEASUREMENT		STANDARD (NEW)	SERVICE LIMIT
Cylinder block	Warpage of deck surface Bore diameter Bore taper Reboring limit	0.07 (0.003) max. 85.00—85.02 (3.3464—3.3472) — —	0.10 (0.004) 85.07 (3.3492) 0.05 (0.002) 0.5 (0.02)
Piston	Skirt O.D. (At 21 mm (0.83 in) from bottom of skirt) Clearance in cylinder No Mark B	84.98—84.99 (3.3456—3.4605) 84.97—84.98 (3.3452—3.3456) 0.02—0.04 (0.0008—0.0016)	84.97 (3.3452) 84.96 (3.3448) 0.05 (0.0020)
Piston ring	Piston-to-ring clearance Ring end gap Top Second Oil	0.035—0.060 (0.0014—0.0024) 0.030—0.055 (0.0011—0.0022) 0.20—0.35 (0.0079—0.0138) 0.40—0.55 (0.0157—0.0217) 0.20—0.70 (0.0079—0.0276)	0.130 (0.0051) 0.130 (0.0051) 0.60 (0.0236) 0.70 (0.0276) 0.80 (0.0315)
Connecting rod	Pin-to rod interference Small end bore diameter Large end bore diameter End play installed on crankshaft 2.0 ℓ 2.2 ℓ	0.013—0.032 (0.0005—0.0013) 21.968—21.981 (0.8649—0.8654) Nominal 48 (1.890) Nominal 51 (2.008) 0.15—0.30 (0.006—0.012)	— — — — 0.40 (0.016)
Crankshaft	Main journal diameter No.1, 2 Journals No.3 Journal No.4 Journal No.5 Journal Taper/out-of-round, main journal Rod journal diameter Taper/out-of-round, rod journal End play Runout 2.0 ℓ 2.2 ℓ	49.976—50.000 (1.9676—1.9685) 49.972—49.996 (1.9674—1.9683) 49.984—50.008 (1.9665—1.9688) 49.984—50.008 (1.9679—1.9688) 49.988—50.012 (1.9680—1.9690) 0.005 (0.0002) max. 44.976—45.000 (1.7710—1.7717) 47.976—48.000 (1.8888—1.8898) 0.005 (0.0002) max. 0.10—0.35 (0.004—0.014) 0.015 max. (0.0006)	— — — — — 0.006 (0.0004) — — 0.006 (0.0004) 0.45 (0.018) 0.020 (0.0008)
Bearings	Main bearing-to journal oil clearance No.1, 2 Journals No.3 Journal No.4 Journal No.5 Journal Rod bearing-to journal oil clearance 2.2 ℓ 2.0 ℓ	0.021—0.045 (0.0009—0.0018) 0.025—0.049 (0.001—0.0019) 0.013—0.037 (0.0005—0.0015) 0.009—0.033 (0.0004—0.0013) 0.021—0.049 (0.0008—0.0019) 0.015—0.043 (0.0006—0.0017)	0.05 (0.002) 0.054 (0.0021) 0.05 (0.002) 0.05 (0.002) 0.05 (0.002) 0.05 (0.002)

# Standards and Service Limits

## 5. Engine/Engine Block

		MEASUREMENT		STANDARD (NEW)		SERVICE LIMIT
Balancer shaft	Journal diameter	No. 1 journal (Front)		42.722—42.734 (1.6820—1.6824)		—
		No. 2 journal (Rear)		20.938—20.950 (0.8243—0.8248)		—
		No. 3 journal		38.712—38.724 (1.5241—1.5246)		—
	Journal taper			34.722—34.734 (1.3670—1.3674)		—
		End play		0.005 (0.0002)		—
	Runout		(Front)	0.100—0.350 (0.0040—0.0138)		—
			(Rear)	0.060—0.180 (0.0024—0.0070)		—
	Oil Clearance			0.020 (0.0008)		—
Balancer shaft bearing	I.D.	No. 1 journal (Front)		42.800—42.820 (1.6850—1.6858)		—
		No. 2 journal (Rear)		21.000—21.013 (0.8268—0.8273)		—
		No. 1, 3 journal		38.800—38.820 (1.5276—1.5283)		—
		No. 2 journal		0.076—0.128 (0.0030—0.0050)		—

## 5. Engine/Engine Lubrication

		MEASUREMENT		STANDARD (NEW)		SERVICE LIMIT
Engine oil	Capacity ℓ (US qt, Imp qt)		4.9 (5.2, 4.3) After engine disassembly 3.8 (4.0, 3.3) After oil change, including oil filter 3.5 (3.7, 3.1) After oil change, without oil filter			
Oil pump	Displacement ℓ(US qt, Imp qt)/min. at pump 1,000 min <sup>-1</sup> (rpm)		7.4 (7.8, 6.5) min.			
	Inner-to-outer rotor radial clearance		0.02—0.16 (0.0008—0.0063)		0.2 (0.008)	
	Pump body-to-rotor radial clearance		0.10—0.19 (0.0040—0.0075)		0.21 (0.0083)	
Relief valve	Pump body-to-rotor side clearance		0.02—0.07 (0.001—0.003)		0.12 (0.005)	
	Pressure setting with oil temperature at 80°C (176°F)	Idle	69 kPa (0.7 kg/cm <sup>2</sup> , 10 psi) min.			
		3,000 min <sup>-1</sup> (rpm)	343 kPa (3.5 kg/cm <sup>2</sup> , 50 psi)			

## 5. Engine/Cooling

	MEASUREMENT	STANDARD (NEW)
Thermostat	Starts to open Full open Valve lift at full open	78±2°C (172±3°F) 90°C (194°F) 8 (0.31) max.
Water pump	Displacement ℓ (US qt, Imp qt)/min. at pump 2,000 min <sup>-1</sup> (rpm)	44 (46, 40) min.
Radiator	Capacity (incl. heater) ℓ (US qt, Imp qt) (Includes reservoir tank 0.6 (0.63, 0.53)) for overhaul 1. F20A2: 2. F20A3: 3. F20A5: 4. F20A6: 5. F20A8: 6. F22A2: 7. F22A3: 8. F22A6: 9. F22A7: 10. F22A8: 11. F22A9: 12. F20A7: 13. F20Z3: for change 1. F20A2: 2. F20A3: 3. F20A5: 4. F20A6: 5. F20A8: 6. F22A2: 7. F22A3: 8. F22A6: 9. F22A7: 10. F22A8: 11. F22A9: 12. F20A7: 13. F20Z3: Pressure cap opening pressure	M/T: 7.2 (7.61, 6.34) A/T: 7.1 (7.50, 6.23) 7.2 (7.61, 6.34) 7.1 (7.50, 6.23) 6.6 (6.97, 5.81)* 7.1 (7.50, 6.23)* 7.2 (7.61, 6.34) 7.1 (7.50, 6.23) 7.2 (7.61, 6.34) 7.1 (7.50, 6.23) 7.2 (7.61, 6.34) 7.1 (7.50, 6.23) 6.6 (6.97, 5.81) 7.1 (7.50, 6.23) 7.2 (7.61, 6.34) 7.1 (7.50, 6.23) 6.6 (6.97, 5.81) 7.1 (7.50, 6.23) 7.2 (7.61, 6.34) 7.1 (7.50, 6.23) 7.2 (7.61, 6.34) 7.1 (7.50, 6.23) M/T: 3.6 (3.80, 3.17) A/T: 3.5 (3.70, 3.08) 3.6 (3.80, 3.17) 3.5 (3.70, 3.08) 3.0 (3.17, 2.64)* 3.5 (3.70, 3.08)* 3.6 (3.80, 3.17) 3.5 (3.70, 3.08) 3.6 (3.80, 3.17) 3.5 (3.70, 3.08) 3.6 (3.80, 3.17) 3.5 (3.70, 3.08) 3.0 (3.17, 2.64) 3.0 (3.17, 2.64) 3.6 (3.80, 3.17) 3.6 (3.80, 3.17) 3.0 (3.17, 2.64) 3.5 (3.70, 3.08) 3.6 (3.80, 3.17) 3.6 (3.80, 3.17) 3.0 (3.17, 2.64) 3.6 (3.80, 3.17) 3.6 (3.80, 3.17) 3.5 (3.70, 3.08) 3.6 (3.80, 3.17) 3.5 (3.70, 3.08) 93–123 kPa (0.95–1.25 kg/cm <sup>2</sup> , 13.5–17.8 psi)
Cooling fan	"ON" temperature "OFF" temperature "ON" temperature (Fan timer) "OFF" temperature (Fan timer)	87°–93°C (189°–199°F) 80°–91°C (176°–196°F) 105°–111°C (221°–231°F) 98°–109°C (208°–228°F)
Radiator cap	Opening pressure kPa (kg/cm <sup>2</sup> , psi)	95-125 (0.95-1.25, 13.5-17.8)

\*KB model

1. F20A2: 2.0 ℓ CARB with CATA
2. F20A3: 2.0 ℓ CARB
3. F20A5: 2.0 ℓ PGM-FI
6. F20A6: 2.0 ℓ CARB with CATA
5. F20A8: 2.0 ℓ PGM-FI with CATA
6. F22A2: 2.2 ℓ PGM-FI
7. F22A3: 2.2 ℓ PGM-FI with CATA
8. F22A6: 2.2 ℓ PGM-FI with CATA for 5D KQ
9. F22A7: 2.2 ℓ PGM-FI with CATA for 5D EC M/T
10. F22A8: 2.2 ℓ PGM-FI with CATA for 5D EC A/T
11. F22A9: 2.2 ℓ PGM-FI with CATA
12. F20A7: 2.0 ℓ PGM-FI with CATA for KB other
13. F20Z3: 2.0 ℓ PGM-FI with CATA for 5D EC

# Standards and Service Limits

## 6. Fuel and Emissions

MEASUREMENT		STANDARD (NEW)
Fuel pump (PGM-FI)	Displacement (minimum in 10 seconds) Relief valve opening pressure	230 ml (7.8 US oz, 8.1 Imp oz) 441–588 kPa (4.5–6.0 kg/cm <sup>2</sup> , 64–85 psi)
Fuel pump (CARB)	Delivery pressure Displacement (minimum in minute at 12V)	9–12 kPa (0.09–0.12 kg/cm <sup>2</sup> , 1.3–1.7 psi) 700 ml (23.7 US oz, 19.7 Imp oz)
Pressure regulator (PGM-FI)	Pressure with regulator vacuum hose disconnected	240–279 kPa (2.45–2.85 kg/cm <sup>2</sup> , 34–41 psi)* <sup>1</sup> 275–324 kPa (2.80–3.30 kg/cm <sup>2</sup> , 40–47 psi)* <sup>2</sup>
Fuel tank	Capacity 2WS: 4WS:	65 ℓ (17.2 US gal, 14.3 Imp gal) 60 ℓ (15.9 US gal, 13.2 Imp gal)
Engine	Fast idle	PGM-FI: 1,400 ± 400 min <sup>-1</sup> (rpm) CARB: 3,400 ± 500 min <sup>-1</sup> (rpm)
	Idle speed (with headlights and cooling fan OFF)	800 ± 50 min <sup>-1</sup> (rpm) 770 ± 50 min <sup>-1</sup> (rpm) 750 ± 50 min <sup>-1</sup> (rpm) in <b>N</b> or <b>P</b> position 770 ± 50 min <sup>-1</sup> (rpm) in <b>N</b> or <b>P</b> position
	Idle CO	With CATA: 0.1% maximum Without CATA: 1.0 ± 1.0%

\*1: F20A5, F22A2, F22A3, F22A7, F22A8 engines

\*2: Except F20A5, F22A2, F22A3, F22A7, F22A8 engines



## 7. Clutch

MEASUREMENT		STANDARD (NEW)	SERVICE LIMIT
Clutch pedal	Pedal height	RHD: 210 (8.3) to floor LHD: 184 (7.2) to floor	— —
	Stroke	142.0 (5.6)	—
	Pedal play	9–15 (0.4–0.6)	—
	Disengagement height	90 (3.5) min. to floor	—
		80 (3.1) min. to carpet	—
Flywheel	Clutch surface runout	0.05 (0.002) max.	0.15 (0.006)
Clutch disc	Rivet head depth	1.3 (0.05) min.	0.2 (0.008)
	Surface runout	0.6 (0.02) max.	1.0 (0.04)
	Thickness	8.4–9.1 (0.33–0.36)	6.0 (0.24)
Clutch cover	Unevenness of diaphragm spring	0.6 (0.02) max.	0.8 (0.03)

## 8. Manual Transmission

MEASUREMENT		STANDARD (NEW)	SERVICE LIMIT	
Transmission oil	Capacity ℓ (US qt, Imp qt)	1.9 (2.0, 1.7) for oil change 2.0 (2.1, 1.8) for overhaul		
Mainshaft	End play	0.10–0.16 (0.0039–0.0063)	Adjust with a shim.	
	Diameter of ball bearing contact area	27.977–27.990 (1.1015–1.1020)	27.940 (1.1000)	
	Diameter of third gear contact area	37.984–38.000 (1.4954–1.4961)	37.930 (1.4933)	
	Diameter of ball bearing contact area	27.987–28.000 (1.1018–1.1024)	27.940 (1.1000)	
	Runout	0.02 (0.0008) max.	0.05 (0.002)	
Mainshaft third and fourth gears	I.D.	43.009–43.025 (1.6933–1.6939)	43.080 (1.6961)	
	End play	0.06–0.21 (0.0024–0.0083)	0.30 (0.012)	
	Thickness	3rd gear	32.42–32.47 (1.276–1.278)	32.3 (1.27)
		4th gear	30.92–30.97 (1.217–1.219)	30.8 (1.21)
Mainshaft fifth gear	I.D.	43.009–43.025 (1.6933–1.6939)	43.080 (1.6961)	
	End play	0.06–0.21 (0.0024–0.0083)	0.30 (0.012)	
	Thickness	30.92–30.97 (1.217–1.219)	30.8 (1.21)	
Countershaft	End play	0.05–0.40 (0.0019–0.0157)	0.50 (0.02)	
	Diameter of needle bearing contact area	38.000–38.015 (1.4961–1.4967)	37.95 (1.4941)	
	Diameter of ball bearing needle bearing contact area	24.987–25.000 (0.9837–0.9845)	24.94 (0.982)	
	Diameter of low gear contact area	39.984–40.000 (1.5742–1.5748)	39.93 (1.572)	
	Runout	0.02 (0.0008) max.	0.05 (0.002)	

## 8. Manual Transmission

	MEASUREMENT	STANDARD (NEW)	SERVICE LIMIT
Countershaft low gear	I.D. End play	46.009–46.025 (1.8114–1.8120) 0.04–0.10 (0.002–0.004)	46.08 (1.814) Adjust with a washer.
Countershaft second gear	I.D. End play Thickness	47.009–47.025 (1.8507–1.8514) 0.04–0.10 (0.002–0.004) 34.62–34.67 (1.3630–1.3650)	47.08 (1.854) Adjust with a collar. 33.5 (1.32)
Spacer collar (Countershaft second gear)	I.D. O.D. Length	36.48–36.49 (1.4362–1.4366) 41.989–42.000 (1.6531–1.6535) 29.02–29.04 (1.1425–1.1433) 29.07–29.09 (1.1445–1.1453)	36.50 (1.437) 41.94 (1.651) — —
Spacer collar (Mainshaft fourth and fifth gears)	I.D. O.D. Length	31.002–31.012 (1.2205–1.2209) 37.989–38.000 (1.4956–1.4961) 56.45–56.55 (2.222–2.226) 26.03–26.08 (1.0248–1.0268)	31.06 (1.223) 37.94 (1.494) — 26.01 (1.024)
		A B	
Reverse idler gear	I.D. Gear-to-reverse gear shaft clearance	20.016–20.043 (0.7880–0.7891) 0.036–0.084 (0.0014–0.0033)	20.09 (0.7909) 0.160 (0.0006)
Synchronizer ring	Ring-to-gear clearance (ring pushed against gear)	0.85–1.10 (0.0335–0.0433)	0.40 (0.016)
Shift fork	Synchronizer sleeve groove width Fork-to-synchronizer sleeve clearance	6.75–6.85 (0.266–0.270) 0.35–0.65 (0.014–0.026)	— 1.0 (0.039)
Reverse shift fork	Pawl groove width Fork-to-reverse idle gear clearance Groove width Fork-to fifth/reverse shift Shaft clearance	13.0–13.3 (0.51–0.52) 0.5–1.1 (0.02–0.43) 7.05–7.25 (0.278–0.2854) 7.4–7.7 (0.29–0.30) 0.05–0.35 (0.002–0.014) 0.4–0.8 (0.02–0.03)	1.8 (0.07). — — 0.5 (0.02) 1.0 (0.04)
		at A at B at A at B	
Shift arm	I.D. Shift arm-to-shaft clearance Shift fork diameter at contact area Shift arm-to-shift fork shaft clearance	15.973–16.000 (0.6289–0.6299) 0.005–0.059 (0.0002–0.0023) 12.9–13.0 (0.508–0.512) 0.2–0.5 (0.01–0.02)	— — — 0.6 (0.02)
Select lever	Pin size of contact area Shaft outer diameter Shift arm cover clearance	7.9–8.0 (0.311–0.315) 15.41–15.68 (0.607–0.617) 0.032–0.102 (0.0013–0.0040)	— — —
Shift arm lever	O.D. Transmission housing clearance	15.941–15.968 (0.6276–0.6287) 0.027–0.139 (0.0011–0.0055)	— —
Inter lock	Bore diameter Shift arm lever clearance	16.00–16.05 (0.630–0.632) 0.032–0.109 (0.0013–0.0043)	— —
Ring gear	Backlash	0.085–0.142 (0.0033–0.0056)	0.200 (0.0079)
Differential carrier	Pinion shaft bore diameter Carrier-to-pinion shaft clearance Driveshaft bore diameter Carrier-to-driveshaft clearance	18.000–18.018 (0.7087–0.7094) 0.017–0.047 (0.0007–0.0019) 28.005–28.025 (1.1026–1.1033) 0.025–0.066 (0.0009–0.0026) 0.055–0.091 (0.0022–0.0036)	— 0.100 (0.0039) — 0.120 0.150
		R L	
Differential pinion gear	Backlash Pinion gear bore diameter Pinion gear-to-pinion shaft clearance	0.05–0.15 (0.002–0.006) 18.042–18.066 (0.7103–0.7113) 0.059–0.095 (0.0023–0.0037)	Selection with 7 types of washers. — 0.150 (0.0059)
Differential taper roller bearing	Preload	1.4–2.6 N·m (14–26 kg·cm, 1.0–1.9 lb·ft)	Selection with 20 types of shims.

# Standards and Service Limits

## 9. Automatic Transmission

		MEASUREMENT	STANDARD (NEW)	SERVICE LIMIT
Transmission oil	Capacity ℓ (US qt, Imp qt)		2.4 (2.5, 2.1) for oil change 6.0 (6.3, 5.3) for overhaul	
Hydraulic pressure	Line pressure at 2,000 min <sup>-1</sup> (rpm) ([N] or [P] position)	Carburetor	760 kPa (7.75 kg/cm <sup>2</sup> , 110 psi) Throttle valve full-closed 809 kPa (8.25 kg/cm <sup>2</sup> , 117 psi) Throttle valve more than 2/8 open	711 kPa (7.25 kg/cm <sup>2</sup> , 103 psi) Throttle valve more than 2/8 open
		PGM-FI	784 kPa (8.0 kg/cm <sup>2</sup> , 114 psi) Throttle valve full-closed 834 kPa (8.5 kg/cm <sup>2</sup> , 121 psi) Throttle valve more than 1.5/8 open	735 kPa (7.5 kg/cm <sup>2</sup> , 107 psi) Throttle valve more than 1.5/8 open
	4th clutch pressure at 2,000 min <sup>-1</sup> (rpm) ([D4] position)	Carburetor	412 kPa (4.2 kg/cm <sup>2</sup> , 60 psi) Throttle valve full-closed 809 kPa (8.25 kg/cm <sup>2</sup> , 117 psi) Throttle valve more than 2/8 open	353 kPa (3.6 kg/cm <sup>2</sup> , 51 psi) Throttle valve full-closed 711 kPa (7.25 kg/cm <sup>2</sup> , 103 psi) Throttle valve more than 2/8 open
		PGM-FI	520 kPa (5.3 kg/cm <sup>2</sup> , 75 psi) Throttle valve full-closed 834 kPa (8.5 kg/cm <sup>2</sup> , 121 psi) Throttle valve more than 1.5/8 open	461 kPa (4.7 kg/cm <sup>2</sup> , 67 psi) Throttle valve full-closed 735 kPa (7.5 kg/cm <sup>2</sup> , 107 psi) Throttle valve more than 1.5/8 open
	3rd clutch pressure at 2,000 min <sup>-1</sup> (rpm) ([D4] or [D3] position)	Carburetor	392 kPa (4.0 kg/cm <sup>2</sup> , 57 psi) Throttle valve full-closed 809 kPa (8.25 kg/cm <sup>2</sup> , 117 psi) Throttle valve more than 2/8 open	353 kPa (3.6 kg/cm <sup>2</sup> , 51 psi) Throttle valve full-closed 711 kPa (7.25 kg/cm <sup>2</sup> , 103 psi) Throttle valve more than 2/8 open
		PGM-FI	490 kPa (5.0 kg/cm <sup>2</sup> , 71 psi) Throttle valve full-closed 834 kPa (8.5 kg/cm <sup>2</sup> , 121 psi) Throttle valve more than 1.5/8 open	441 kPa (4.5 kg/cm <sup>2</sup> , 64 psi) Throttle valve full-closed 735 kPa (7.5 kg/cm <sup>2</sup> , 107 psi) Throttle valve more than 1.5/8 open
	2nd clutch pressure at 2,000 min <sup>-1</sup> (rpm) ([D4] or [D3] position)	Carburetor	392 kPa (4.0 kg/cm <sup>2</sup> , 57 psi) Throttle valve full-closed 809 kPa (8.25 kg/cm <sup>2</sup> , 117 psi) Throttle valve more than 2/8 open	353 kPa (3.6 kg/cm <sup>2</sup> , 51 psi) Throttle valve full-closed 711 kPa (7.25 kg/cm <sup>2</sup> , 103 psi) Throttle valve more than 2/8 open
		PGM-FI	490 kPa (5.0 kg/cm <sup>2</sup> , 71 psi) Throttle valve full-closed 834 kPa (8.5 kg/cm <sup>2</sup> , 121 psi) Throttle valve more than 1.5/8 open	441 kPa (4.5 kg/cm <sup>2</sup> , 64 psi) Throttle valve full-closed 735 kPa (7.5 kg/cm <sup>2</sup> , 107 psi) Throttle valve more than 1.5/8 open
	1st clutch pressure at 2,000 min <sup>-1</sup> (rpm) ([1], [D4] or [D3] position)	Carburetor	760–809 kPa (7.75–8.25 kg/cm <sup>2</sup> , 110–117 psi)	711 kPa (7.25 kg/cm <sup>2</sup> , 103 psi)
		PGM-FI	785–834 kPa (8.0–8.5 kg/cm <sup>2</sup> , 114–121 psi)	735 kPa (7.5 kg/cm <sup>2</sup> , 107 psi)
	2nd clutch pressure at 2,000 min <sup>-1</sup> (rpm) ([2] position)	Carburetor	760–809 kPa (7.75–8.25 kg/cm <sup>2</sup> , 110–117 psi)	711 kPa (7.25 kg/cm <sup>2</sup> , 103 psi)
		PGM-FI	785–834 kPa (8.0–8.5 kg/cm <sup>2</sup> , 114–121 psi)	735 kPa (7.5 kg/cm <sup>2</sup> , 107 psi)

## 9. Automatic Transmission

MEASUREMENT		STANDARD (NEW)		SERVICE LIMIT	
Hydraulic pressure	Governor pressure at 60 km/h (37.5 mph) (D <sub>4</sub> or D <sub>3</sub> position)	Carburetor with CATA	226–235 kPa (2.30–2.40 kg/cm <sup>2</sup> , 33–34 psi)	221 kPa (2.25 kg/cm <sup>2</sup> , 32 psi)	
		Carburetor without CATA	167–177 kPa (1.70–1.80 kg/cm <sup>2</sup> , 24–25 psi)	162 kPa (1.65 kg/cm <sup>2</sup> , 23 psi)	
	Throttle pressure A (D <sub>4</sub> or D <sub>3</sub> position)	Carburetor with CATA	closed 0 open 515–530 kPa (5.25–5.4 kg/cm <sup>2</sup> , 75–77 psi)	— 510 kPa (5.2 kg/cm <sup>2</sup> , 74 psi)	
		Carburetor without CATA	closed 0 open 485–500 kPa (4.95–5.10 kg/cm <sup>2</sup> , 70–73 psi)	— 481 kPa (4.9 kg/cm <sup>2</sup> , 70 psi)	
	Throttle pressure B (D <sub>4</sub> or D <sub>3</sub> position)	Carburetor	closed 0	—	
			open 760–809 kPa (7.75–8.25 kg/cm <sup>2</sup> , 110–117 psi)	711 kPa (7.25 kg/cm <sup>2</sup> , 103 psi)	
		PGM-FI	closed 0 open 785–834 kPa (8.0–8.5 kg/cm <sup>2</sup> , 114–121 psi)	— 735 kPa (7.5 kg/cm <sup>2</sup> , 107 psi)	
	Stall speed	Check with car on level ground	Carburetor	2,450–2,750 min <sup>-1</sup> (rpm)	—
			PGM-FI	2,350–2,650 min <sup>-1</sup> (rpm)	—
Clutch	Clutch initial clearance	1st-hold	0.8–1.0 (0.031–0.039)	—	
		1st, 2nd	0.65–0.85 (0.026–0.033)	—	
		3rd, 4th	0.4–0.6 (0.016–0.024)	—	
	Clutch return spring free length	Carburetor	1st, 2nd, 3rd: 33.9 (1.33) 4th: 30.2 (1.189)	31.9 (1.256) 28.2 (1.110)	
		PGM-FI	1st, 2nd, 3rd, 4th: 33.5 (1.318)	31.5 (1.240)	
	Clutch disc thickness		1.88–2.0 (0.074–0.079)	Until grooves worn out	
	Clutch plate thickness	Carburetor	1st, 2nd: 2.25–2.35 (0.089–0.093)	Discoloration ↑ ↓ Discoloration	
			3rd, 4th, 1st-hold: 1.95–2.05 (0.077–0.081)		
		PGM-FI	1st, 1st-hold: 1.95–2.05 (0.0767–0.0807)		
			2nd: 2.55–2.65 (0.1003–0.1043) 3rd, 4th: 2.25–2.35 (0.0885–0.0925)		
Clutch end plate thickness	Mark 1	2.05–2.10 (0.081–0.83)			
	Mark 2	2.15–2.20 (0.085–0.087)			
	Mark 3	2.25–2.30 (0.089–0.091)			
	Mark 4	2.35–2.40 (0.093–0.094)			
	Mark 5	2.45–2.50 (0.096–0.098)			
	Mark 6	2.55–2.60 (0.100–0.102)			
	Mark 7	2.65–2.70 (0.104–0.106)			
	Mark 8	2.75–2.80 (0.108–0.110)			
	Mark 9	2.85–2.90 (0.112–0.114)			
	*Mark 10	2.95–3.00 (0.116–0.118)			

\*Carbureted engine only.

# Standards and Service Limits

## 9. Automatic Transmission (cont'd)

	MEASUREMENT	STANDARD (NEW)	SERVICE LIMIT
Valve body	Stator camshaft needle bearing contact area I.D. (torque converter side)	27.000—27.021 (1.0630—1.0638)	Wear or damage
	Stator camshaft needle bearing contact area I.D. (oil pump side)	29.000—29.013 (1.1417—1.1422)	—
	Oil pump driven gear I.D.	14.016—14.034 (0.5518—0.5525)	Wear or damage
	Oil pump gear shaft O.D.	13.980—13.990 (0.5504—0.5508)	Wear or damage
	Oil pump gear side clearance	0.03—0.05 (0.0012—0.0020)	0.07 (0.0028)
	Oil pump gear-to-body clearance	0.21—0.265 (0.0083—0.0104)	—
	Drive Driven	0.07—0.125 (0.0027—0.0049)	—
Regulator valve body	Sealing ring contact area diameter	35.000—35.025 (1.3780—1.3789)	35.050 (1.3799)
Accumulator body	Sealing ring contact area diameter	32.000—32.013 (1.2598—1.2604)	32.05 (1.2618)
Stator camshaft	Sealing ring contact area diameter	29.000—29.013 (1.1417—1.1422)	29.05 (1.1436)
Shifting device and parking brake control	Reverse shift fork thickness	5.90—6.00 (0.232—0.236)	5.40 (0.213)
	Parking brake ratchet pawl	—	Wear or other defect
	Parking gear	—	Wear or other defect
	Throttle cam stopper	18.5—18.6 (0.7283—0.7322)	—
	Carburetor PGM-FI	17.0—17.1 (0.6692—0.6732)	—
Servo body	Shift fork shaft I.D.	A	14.000—14.005 (0.5512—0.5514)
		B	14.006—14.010 (0.5514—0.5516)
		C	14.011—14.015 (0.5516—0.5518)
	Shift fork shaft valve bore I.D.	37.000—37.039 (1.4567—1.4582)	37.045 (1.4585)
Transmission	Diameter of needle bearing contact area	22.984—23.000 (0.9049—0.9055)	Wear or damage ↑ ↓ Wear or damage
	On mainshaft and stator shaft	31.984—32.000 (1.2592—1.2598)	
	On mainshaft 4th gear collar	41.984—42.000 (1.6529—1.6535)	
	On mainshaft 3rd gear collar	45.984—46.000 (1.8104—1.8110)	
	Carburetor PGM-FI	40.984—41.000 (1.6142—1.6535)	
	On countershaft 1st gear collar	31.975—31.991 (1.2589—1.2595)	
	On countershaft 4th gear	35.979—36.000 (1.4165—1.4173)	
	On countershaft reverse gear	39.984—40.000 (1.5741—1.5748)	
	On countershaft parking gear	31.975—31.991 (1.2588—1.2594)	
	On secondary shaft 1st gear	31.975—31.991 (1.2588—1.2594)	
	On secondary shaft 2nd gear	14.416—14.434 (0.5675—0.5682)	
	Reverse idler gear shaft holder I.D.	48.000—48.019 (1.8898—1.8905)	
	Mainshaft 3rd gear I.D.	52.000—52.019 (2.0472—2.0480)	
Carburetor PGM-FI	38.005—38.021 (1.4963—1.4969)		
Mainshaft 4th gear I.D.			

## 9. Automatic Transmission

	MEASUREMENT	STANDARD (NEW)	SERVICE LIMIT
Transmission	Countershaft 1st gear I.D.	47.000—47.016 (1.8504—1.8510)	Wear or damage  Wear or damage
	Countershaft 4th gear I.D.	38.000—38.016 (1.4961—1.4967)	
	Countershaft reverse gear I.D.	42.000—42.016 (1.6535—1.6541)	
	Countershaft idler gear I.D.	48.000—48.016 (1.8897—1.8903)	
	Secondary shaft 1st gear I.D.	37.000—37.016 (1.4566—1.4573)	
	Secondary shaft 2nd gear I.D.	37.000—37.016 (1.4566—1.4573)	
	Mainshaft 3rd gear collar length	20.000—20.050 (0.7874—0.7893)	
	Mainshaft 3rd gear collar length	19.500—19.550 (0.7677—0.7697)	
	Mainshaft 4th gear collar length	47.500—47.550 (1.8700—1.8720)	
	Countershaft 1st gear collar length	27.500—27.550 (1.0826—1.0846)	
	Secondary shaft distance collar length	4.95—5.00 (0.1948—0.1968)	
	Secondary shaft 2nd gear thrust washer thickness	4.35—4.45 (0.1713—0.1752)	
	Countershaft 1st gear thrust washer thickness	1.45—1.50 (0.0570—0.0590)	
	Countershaft idler gear thrust washer thickness	3.45—3.55 (0.1358—0.1398)	
	Countershaft parking gear length	25.030—25.048 (0.9854—0.9861)	
	Secondary shaft 2nd gear spline washer thickness	4.02—4.05 (0.158—0.159)	
		4.07—4.10 (0.160—0.161)	
		4.12—4.15 (0.162—0.163)	
		4.17—4.20 (0.164—0.165)	
		4.22—4.25 (0.166—0.167)	
	4.27—4.30 (0.168—0.169)		
	4.32—4.35 (0.170—0.171)		
	4.37—4.40 (0.172—0.173)		
	4.42—4.45 (0.174—0.175)		

# Standards and Service Limits

Unit of length: mm (in)

## 9. Automatic Transmission (cont'd)

	MEASUREMENT	STANDARD (NEW)				
		WIRE DIA.	O.D.	FREE LENGTH	No. of COILS	
Spring (Carburetor)	One way ball spring	0.29 (0.0114)	4.0 (0.1574)	14.0 (0.5511)	13.0	
	Regulator valve spring A	1.80 (0.0708)	14.7 (0.5787)	86.5 (3.4055)	16.5	
	Regulator valve spring B	1.80 (0.0708)	9.6 (0.3779)	44.0 (1.7328)	7.5	
	Stator reaction spring	5.50 (0.2165)	37.4 (1.4724)	30.3 (1.1929)	2.1	
	Throttle modulator spring	1.20 (0.0472)	9.4 (0.3700)	27.2 (1.0708)	8.0	
		with CATA	1.20 (0.0472)	9.4 (0.3700)	26.3 (1.0354)	8.0
		without CATA	1.10 (0.0433)	8.4 (0.3307)	36.4 (1.4331)	12.0
	Torque convertor check valve spring	1.00 (0.0393)	8.4 (0.3307)	39.1 (1.5393)	15.1	
	Relife valve spring	1.10 (0.0433)	8.4 (0.3307)	46.8 (1.8425)	17.0	
	Cooler check valve spring	1.0 (0.0393)	18.8 (0.7401)	25.8 (1.0157)	4.0	
	Governor spring A	1.0 (0.0393)	18.8 (0.7401)	41.2 (1.6220)	4.0	
		without CATA	1.0 (0.0393)	18.8 (0.7401)	44.3 (1.7440)	4.0
		with CATA	0.8 (0.0314)	11.8 (0.4645)	22.9 (0.9016)	7.0
	Governor spring B	0.9 (0.0354)	11.8 (0.4645)	18.4 (0.7244)	6.2	
		without CATA	0.9 (0.0354)	11.8 (0.4645)	21.4 (0.8425)	6.2
	2nd orifice control spring	0.7 (0.0275)	6.6 (0.2598)	53.3 (2.0984)	20.5	
	Servo orifice control spring	0.9 (0.0354)	7.1 (0.2795)	61.2 (2.4094)	28.2	
	Throttle spring A	1.0 (0.0393)	8.5 (0.3346)	21.0 (0.8267)	5.8	
		1.0 (0.0393)	8.5 (0.3346)	21.0 (0.8267)	5.4	
		1.0 (0.0393)	8.5 (0.3346)	22.2 (0.8740)	6.0	
		1.0 (0.0393)	8.5 (0.3346)	22.1 (0.8701)	5.5	
	Throttle adjust spring A	0.8 (0.0314)	6.2 (0.2440)	27.0 (1.0630)	8.5	
	Throttle adjust spring B	0.8 (0.0314)	6.2 (0.2440)	30.0 (1.1811)	8.0	
	Throttle spring B	1.4 (0.0551)	8.5 (0.3346)	41.6 (1.6378)	14.0	
	1-2 shift spring	0.5 (0.0196)	4.6 (0.1811)	42.3 (1.6653)	25.0	
		with CATA	0.6 (0.0236)	6.1 (0.2401)	42.3 (1.6653)	21.1
		without CATA	0.4 (0.0157)	4.5 (0.1771)	13.0 (0.5118)	8.7
	1-2 shift ball spring	0.4 (0.0157)	4.5 (0.1771)	12.6 (0.4960)	8.7	
	2-3 shift spring	0.9 (0.0354)	7.6 (0.2992)	70.0 (2.7559)	28.2	
		with CATA	0.8 (0.0314)	7.6 (0.2992)	58.9 (2.3188)	16.8
	2-3 shift ball spring	0.5 (0.0196)	4.5 (0.1771)	11.7 (0.4606)	10.5	
		with CATA	0.5 (0.0196)	4.5 (0.1771)	14.1 (0.5551)	10.5
		without CATA	0.9 (0.0354)	9.6 (0.3779)	35.8 (1.4094)	10.3
	3-4 shift spring	0.9 (0.0354)	9.6 (0.3779)	27.7 (1.0905)	10.3	
	3-4 shift ball spring	0.5 (0.0196)	4.5 (0.1771)	11.5 (0.4527)	7.4	
		with CATA	0.5 (0.0196)	4.5 (0.1771)	11.3 (0.4448)	7.4
		without CATA	4.0 (0.1574)	21.5 (0.8464)	71.7 (2.8228)	8.3
	1st-hold accumulator spring	1.8 (0.0709)	16.3 (0.6417)	115.4 (4.5433)	18.6	
	1st accumulator spring	2.6 (0.1023)	16.0 (0.6292)	84.6 (3.3307)	14.3	
	4th accumulator spring	3.5 (0.1378)	22.0 (0.8661)	77.1 (3.0354)	10.0	
	2nd accumulator spring	2.6 (0.1023)	17.5 (0.6890)	78.6 (3.0944)	11.0	
	3rd accumulator spring	0.9 (0.0354)	7.6 (0.2992)	73.7 (2.9015)	32.0	
	L/C shift spring	1.0 (0.0393)	6.6 (0.2598)	84.0 (3.3070)	42.4	
	L/C timing spring B	1.0 (0.0393)	6.6 (0.2598)	79.1 (3.1141)	42.4	
	L/C timing spring A	0.9 (0.0354)	6.6 (0.2598)	55.9 (2.2007)	27.3	
		with CATA	0.9 (0.0354)	6.6 (0.2598)	50.0 (1.9685)	27.3
		without CATA	0.8 (0.0314)	7.6 (0.2992)	44.5 (1.7519)	17.0
	Governor cut spring	0.7 (0.0275)	6.6 (0.2598)	42.9 (1.6889)	14.1	
	L/C control spring	1.4 (0.0551)	9.4 (0.3700)	31.2 (1.2283)	10.9	
	CPC valve spring	0.9 (0.0354)	7.6 (0.2992)	62.7 (2.4684)	27.5	
	3rd kick down spring	0.7 (0.0275)	7.1 (0.2795)	40.0 (1.5748)	20.8	
	Reverse control spring	0.7 (0.0275)	7.6 (0.2992)	31.0 (1.2204)	12.7	
	L/C cut spring	1.2 (0.0472)	7.7 (0.3031)	45.6 (1.7952)	21.8	
	Accumulator control spring	1.2 (0.0472)	7.1 (0.2795)	46.9 (1.8464)	20.6	
	2nd kick down spring	0.9 (0.0354)	6.4 (0.2519)	32.5 (1.2795)	17.5	
Servo control spring	0.7 (0.0275)	5.6 (0.2204)	33.0 (1.2992)	21.7		
2-1 timing spring	0.8 (0.0314)	6.1 (0.2401)	51.1 (2.0118)	26.6		
4th exhaust spring						

## 9. Automatic Transmission

	MEASUREMENT	STANDARD (NEW)				
		WIRE DIA.	O.D.	FREE LENGTH	No. of COILS	
Spring (PGM-FI)	Regulator valve spring	A	1.8 (0.0709)	14.7 (0.5887)	86.5 (3.4055)	16.5
		B	1.8 (0.0709)	9.6 (0.3779)	44.0 (1.7323)	12.7
	Stator reaction spring		4.5 (0.1772)	35.4 (1.3937)	30.3 (1.1929)	1.92
	Torque converter check valve spring		1.1 (0.0433)	8.4 (0.3307)	36.4 (1.4331)	12.0
	Relief valve spring		1.0 (0.0394)	8.4 (0.3307)	39.1 (1.5393)	15.1
	Cooler check valve spring		1.1 (0.0433)	8.4 (0.3307)	46.8 (1.8425)	17.0
	2nd orifice control spring		0.6 (0.0236)	6.6 (0.2598)	58.3 (2.2953)	15.8
	Servo orifice control spring		0.8 (0.0315)	6.6 (0.2598)	52.5 (2.0669)	33.0
	4th exhaust spring		0.9 (0.0354)	7.1 (0.2795)	60.8 (2.3936)	28.9
	1-2 shift spring		1.0 (0.0393)	8.6 (0.3386)	41.3 (1.6259)	16.9
	2-3 shift spring		0.9 (0.0354)	7.6 (0.2992)	57.0 (2.2440)	26.8
	1st accumulator spring		1.8 (0.0709)	16.3 (0.6417)	115.4 (4.5433)	18.6
	4th accumulator spring		2.9 (0.1142)	22.0 (0.8661)	90.1 (3.5472)	10.9
	2nd accumulator spring	Sedan	3.5 (0.1378)	22.0 (0.8661)	77.1 (3.0354)	10.0
	2nd accumulator spring	Aero deck	3.3 (0.1299)	22.0 (0.8661)	84.9 (3.3425)	11.1
	3rd accumulator spring	Sedan	2.8 (0.1102)	17.5 (0.6890)	94.2 (3.7086)	16.1
	3rd accumulator spring	Aero deck	2.6 (0.1024)	17.5 (0.6890)	104.5 (4.1142)	18.0
	L/C shift spring		0.9 (0.0354)	7.6 (0.2992)	73.7 (2.9016)	32.0
	L/C timing spring		0.8 (0.0314)	6.6 (0.2598)	51.1 (2.0118)	14.7
	Servo control spring		1.0 (0.0394)	8.1 (0.3188)	52.6 (2.0708)	22.4
	3rd kick-down spring		1.1 (0.0433)	7.6 (0.2992)	48.3 (1.9015)	23.3
	2nd kick-down spring		1.2 (0.0472)	7.1 (0.2795)	46.9 (1.8464)	20.6
	Throttle adjust spring		0.8 (0.0314)	6.2 (0.2440)	30.0 (1.1811)	8.0
	Throttle B spring		1.4 (0.0551)	8.5 (0.3346)	41.5 (1.6339)	10.5
			1.4 (0.0551)	8.5 (0.3346)	41.5 (1.6339)	11.2
			1.4 (0.0551)	8.5 (0.3346)	41.6 (1.6378)	12.4
	1st-hold accumulator spring		4.0 (0.1574)	25.0 (0.9842)	64.7 (2.5472)	7.3
	CPC valve spring		1.4 (0.0551)	9.4 (0.3700)	33.0 (1.2992)	10.5
	L/C control spring		0.7 (0.0276)	6.6 (0.2598)	38.0 (1.4961)	14.1

# Standards and Service Limits

## 9. Automatic Transmission (cont'd)

	MEASUREMENT	STANDARD (NEW)	SERVICE LIMIT
Final driven gear	Backlash	0.085–0.142 (0.003–0.006)	0.200 (0.008)
Differential carrier	Pinion shaft bore diameter	18.000–18.018 (0.7087–0.7094)	—
	Carrier-to-pinion shaft clearance	0.017–0.047 (0.001–0.002)	0.100 (0.004)
	Driveshaft bore diameter	28.005–28.025 (1.1026–1.1033)	—
	Carrier-to driveshaft clearance	0.025–0.066 (0.001–0.003)	0.120 (0.005)
Differential pinion gear	Backlash	0.05–0.15 (0.02–0.006)	Adjust with a washer
	Pinion gear bore diameter	18.042–18.066 (0.710–0.711)	—
	Pinion gear-to pinion shaft clearance	0.059–0.095 (0.002–0.004)	0.120 (0.005)
Differential tapered roller bearing preload	Starting torque	2.5–3.7 N·m (25–37 kg-cm, 1.8–2.7 lb-ft)	Adjust with a washer
	For used bearing After replacement of bearing	2.8–4.0 N·m (28–48 kg-cm, 2.0–2.9 lb-ft)	Adjust with a washer

## 11. Steering

	MEASUREMENT	STANDARD (NEW)
Steering wheel	Play	10 (0.39) maximum
Gearbox	Pinion starting torque	Below 1.0 N·m (10 kg-cm, 0.72 lb-ft)
	Angle of rack guide screw loosend from locked position	20° ± 5° 0
Pump	Pump pressure with valve closed (oil temperature: 40°C/104°F minimum) Do not run for more than 5 seconds	7,845–8,826 kPa (80–90 kg/cm <sup>2</sup> , 1,138–1,280 psi) at idle
Power steering fluid	Capacity Reservoir At change (approx.)	0.5 ℓ (0.53 US qt, 0.44 Imp qt) 1.8 ℓ (1.90 US qt, 1.58 Imp qt)
Power steering belt*	Deflection between pulleys with 98 N (10 kg, 22 lbs) force	For used belt: 13.0–16.0 (0.51–0.62) For new belt: 9.5–11.5 (0.37–0.45)
	Belt tension between pulleys (measured with belt tension gauge)	For used belt: 343–490 N (35–50 kg, 77–110 lbs) For new belt: 686–882 N (70–90 kg, 154–198 lbs)

\*When using a new belt, adjust deflection or tension to new values. Run the engine for 5 minutes then turn it off. Readjust deflection or tension to used belt values.

## 12. Suspension

	MEASUREMENT	STANDARD (NEW)	SERVICE LIMIT		
Wheel alignment	Total toe	Front	0 ± 2 (0 ± 0.08)	—	
		Rear	2WS: IN 2 ± 2 (0.08 ± 0.08) 4WS: IN 3 ± 2 (0.12 ± 0.08)	—	
	Camber	Front	0°00' ± 1°	—	
		Rear	2WS: -0°30' ± 1° 4WS: -0°20' ± 1°	—	
	Caster	Front	3°00' ± 1°	—	
		Front Wheel turning angle	Inward wheel	2WS: 39°05' ± 2° 4WS: 38°50' ± 2°	—
	Outward wheel (reference)		2WS: 29°30' 4WS: 29°30'	—	
	Rear Wheel turning angle (4WS only)	Inward wheel	5° 50' ± 1'	—	
Outward wheel (reference)		6° 10' ± 1'	—		
Wheel	Rim runout	Steel wheel	Below 1.0 (0.04)	2.0 (0.08)	
		Aluminum wheel	Axial	Below 1.0 (0.04)	1.5 (0.06)
			Axial	Below 0.7 (0.03)	2.0 (0.08)
		Radial	Below 0.7 (0.03)	1.5 (0.06)	
Wheel bearing	End play	Front: 0–0.05 (0–0.002) Rear: 0–0.05 (0–0.002)	—		

Unit of length: mm (in)

### 13. Brakes

MEASUREMENT		STANDARD (NEW)		SERVICE LIMIT	
Parking brake lever	Play in stroke 200 N (20 kg, 44 lbs)	To be locked when pulled 4-8 notches		—	
Foot brake pedal	Pedal height (from floor)	LHD: M/T A/T	165 ± 0.5 (6.5 ± 0.02) 170 ± 0.5 (6.7 ± 0.02)	— —	
	Free play	RHD: M/T A/T	190 (7.5) minimum 195 (7.7) minimum	— 5 (0.20)	
Master cylinder	Piston-to-push rod clearance	0-0.4 (0-0.016)		—	
Brake drum	I.D.	220 (8.66)		221 (8.70)	
Lining	Thickness	4.5 (0.18)		2.0 (0.08)	
Disc brake	Disc thickness	Front	23.0 (0.91)	21.0 (0.83)	
		Rear	10.0 (0.39)	8.0 (0.32)	
	Disc runout	Front	—	0.10 (0.004)	
		Rear	—	0.10 (0.004)	
	Disc parallelism	Front and rear	—	0.015 (0.0006)	
Pad thickness	Front	2.0 l model: 12.5 (0.49) 2.2 l model: 12.0 (0.47)	1.6 (0.06) 1.6 (0.06)		
	Rear	9.0 (0.35)	1.6 (0.06)		
Brake booster	Characteristics at 20 kg (44 lbs) pedal pressure	Line pressure Unit: kPa (kg/cm <sup>2</sup> /psi)			
		Vacuum	Brakes	Conventional type	with anti-lock-brake system
		0 mm (0 in) Hg	922 (9.4/134) minimum	813 (8.3/118) minimum	813 (8.3/118) minimum
300 mm (11.8 in) Hg	5,494 (56/796) minimum	6,076 (62/882) minimum	6,076 (62/882) minimum		
500 mm (19.7 in) Hg	8,535 (87/1,237) minimum	8,134 (83/1,180) minimum	8,134 (83/1,180) minimum		

### 15. Air Conditioner

MEASUREMENT		STANDARD (NEW)	
Air conditioner system	Lubricant capacity	Condenser Evaporator Line or hose Reservoir	10 ml (0.3 US oz, 0.4 Imp oz) 25 ml (0.8 US oz, 0.9 Imp oz) 10 ml (0.3 US oz, 0.4 Imp oz) 10 ml (0.3 US oz, 0.4 Imp oz)
Compressor	Lubricant capacity Stator coil resistance at 20°C (68°F) Pulley-to pressure plate clearance	90-120 ml (3.0-4.0 US oz, 3.2-4.2 Imp oz) 3.4-3.8 Ω 0.35-0.65 (0.014-0.026)	
Compressor belt*	Deflection between pulleys with 98N (10 kg, 22 lbs) force	For used belt For new belt	10-12 (0.4-0.5) 4.5-7.0 (0.18-0.28)
	Belt tension between pulleys (measured with belt tension gauge)	For used belt For new belt	441-588 N (45-60 kg, 99-132 lbs) 931-1,127 N (95-115 kg, 209-254 lbs)

\*When using a new belt, adjust deflection or tension to new values. Run the engine for 5 minutes then turn it off. Readjust deflection or tension to used belt values.

# Standards and Service Limits

Unit of length: mm (in)

## 16. Electrical

MEASUREMENT		STANDARD (NEW)	SERVICE LIMIT	
Ignition coil	Rated voltage	12 Volts		
	Winding resistance	Primary	0.6–0.8 Ω <0.5–0.7 Ω>	
		Secondary	12.8–19.2 kΩ <14.4–21.6 kΩ>	
		.< >: Carbureted engine		
Ignition wire	Resistance	25 kΩ maximum		
Spark plug	Type ( ): Manufacturer	Standard	ZFR5F-11 (NGK) or KJ16CR-L11 (ND)* <sup>1</sup> ZFR6F-11 (NGK) or KJ20CR-L11 (ND)* <sup>2</sup>	
		Option	ZFR5F-11 (NGK) or KJ16CR-L11 (ND)* <sup>3</sup> ZFR6F-11 (NGK) or KJ20CR-L11 (ND)* <sup>1</sup> ZFR7F-11 (NGK) or KJ22CR-L11 (ND)* <sup>2</sup>	
	Gap	1.0–1.1 (0.039–0.043)		
Ignition timing	At idling	PGM-FI engine: 15° ± 2° BTDC Carbureted engine: F20A2, F20A3-M/T, F20A6: 15° ± 2° BTDC F20A3-A/T (KY): 0° ± 2° BTDC F20A3-A/T (others): 10° ± 2° BTDC		
Battery	Lighting capacity (20-hours ratio) < >: KY, KQ (except 5D), KP, KT	65Ah <47Ah>		
	Starting capacity (voltage after 5 sec.)	8.4 V minimum/300 ampere draw at –15°C (59°F)		
Alternator	Output < >: Carbureted engine (except KS, KU, KW, KY)	80A <70A>		
	Rotor coil resistance Slip ring O.D. Brush length Brush spring tension	2.8–3.0 Ω 14.4 (0.57) 10.5 (0.41) 300–360 g (10.6–12.7 oz)	14.0 (0.55) 5.5 (0.22)	
Alternator belt*	Deflection at midway between pulleys with 98 N (10 kg, 22 lb) force	Model without A/C	Used belt	10–12 (0.39–0.47)
			New belt	8.5–11 (0.33–0.43)
		Model with A/C	Used belt	10–12 (0.39–0.47)
			New belt	4.5–7.0 (0.18–0.28)
	Belt tension between pulleys (measured with tension gauge)	Model without A/C	Used belt	294–441 N (30–45 kg, 66–99 lb)
			New belt	441–637 N (45–65 kg, 99–143 lb)
Model with A/C		Used belt	441–637 N (45–65 kg, 99–143 lb)	
		New belt	931–1,128 N (95–115 kg, 209–154 lb)	
Starting motor	Output	4D European except KE Except European and KE 5D KE Except KE	M/T: 1.4 kW (2.2 ℓ: 1.6 kW) A/T: 1.6 kW M/T: 1.4 kW A/T: 1.4 kW M/T: 1.4 kW A/T: 1.4 kW M/T: 1.6 kW A/T: 1.6 kW	
	Manufacturer: Mitsuba	Mica depth Commutator runout Commutator O.D. Brush length Brush spring tension	0.4–0.5 (0.016–0.02) 0–0.02 (0–0.001) 28.0–28.1 (1.10–1.11) 15.8–16.2 (0.62–0.64) 16–18 N (1.6–1.8 kg, 3.5–4.0 lbs)	
	Manufacturer: ND	Mica depth Commutator runout Commutator O.D. Brush length Brush spring tension	0.5–0.8 (0.02–0.03) 0–0.02 (0–0.001) 29.9–30.0 (1.18–1.18) 15.0–15.5 (0.59–0.61) 19–24 N (1.9–2.4 kg, 4.2–5.3 lbs)	

\*When using a new belt, adjust deflection or tension to new values. Run the engine for 5 minutes then turn it off. Readjust deflection or tension to used belt values.

\*1: Carburetor type except models for Europe, KY and KU.

\*2: All fuel injection types, and carburetor types for Europe, KY and KU.

\*3: Fuel injection types except 2.2 ℓ models for Europe, and carburetor types for Europe, KY and KU.